

## 3 Way PVC ball valve



Shown with mounting kit for actuator

**Specifications:**

|           |                      |   |  |
|-----------|----------------------|---|--|
| GENERAL   | VALVE TYPE           | 3 WAY 1/4 TURN BALL VALVE                     |  |
|           | VALVE MODEL          | BV-3W-PS4                                     |  |
|           | OPERATOR             | HAND OPERATED WITH LEVER, OR BY ACTUATOR      |  |
|           | DESIGN STANDARDS     | MANUFACTURERS OWN, BASED ON ISO521 1/ DIN3337 |  |
|           | FACE TO FACE DIMS    | MANUFACTURERS OWN                             |  |
|           | TESTING STANDARDS    | MANUFACTURERS OWN                             |  |
|           | CERTIFICATION        | CERTIFICATE OF CONFORMITY ONLY                |  |
|           | ACTUATOR MOUNTING    | MOUNTS WITH MOUNTING KIT                      |  |
|           | SIZE RANGE           | 1/2" UP TO 2"                                 |  |
|           | PRESSURE RATING      | PN10  |  |
|           | TEMPERATURE LIMITS   | WORKING PRESSURE BASED AT 20C                 |  |
| MATERIALS | BODY                 | PVC   |  |
|           | BALL                 | PVC   |  |
|           | STEM(BLOW-OUT PROOF) | PVC   |  |
|           | SEATS                | PTFE  |  |
|           | SEALS                | EPDM OR VITON                                 |  |
|           | END CONNECTIONS      | SOLVENT SOCKET OR BSPP                        |  |
| FEATURES  | ANTI-STATIC DEVICE   | NO  |  |
|           | FIRE SAFE            | NO  |  |
|           | PRIMARY STEM SEAL    | RUBBER O RING                                 |  |
|           | SECONDARY STEM SEAL  | RUBBER O RING                                 |  |
|           | STEM SEAL ADJUSTMENT | NO  |  |
|           | IN-LINE MAINTAINABLE | NO  |  |
| OTHER     |                      |   |  |

**3 Way ball valves –flow patterns:**

