


SIZE	A	B	C	D	F	G	H	W	ACT.
1/4	167	147	42	23	64	47	212	104	J2-20DPS
3/8	167	147	42	23	64	47	212	104	J2-20DPS
1/2	167	147	42	23	66	47	212	104	J2-20DPS
3/4	167	147	48	25	76	50	220	104	J2-20DPS
1	167	147	57	28	86	57	232	104	J2-20DPS
1 1/4	167	147	61	35	103	69	243	104	J2-20DPS
1 1/2	167	147	78	39	119	79	264	104	J2-20DPS
2	167	195	85	46	131	91	326	106	J2-55DPS
2 1/2	167	195	109	59	164	119	363	106	J2-55DPS
3	235	252	118	67	183	122	437	214	J2-140DPS
4	235	252	133	95	236	135	480	214	J2-140DPS

SPECIFICATIONS			
VALVE		ELECTRIC ACTUATOR	
BODY	316 Stainless steel	PROTECTION RATING	IP65 (Weatherproof)
SEATS	RTFE	VOLTAGES	12V DC to 240v AC
SEALS	RTFE	MANUAL OVERRIDE	Standard Across Range
ENDS	BSPP (SW & BW option)	VOLT FREE CONTACTS	Standard Across Range (2-off)
 <div style="border: 1px solid black; padding: 2px; font-size: 8px;"> All Dimensions In mm. Uncontrolled Copy, Not Subject To Automatic Update E&OE </div>		VISUAL INDICATOR	Standard Across Range
		DUTY RATING	100%
		ON POWER FAILURE	Stays put
		CONNECTION	All external by Din plug

316 STAINLESS STEEL BALL VALVE WITH MODULATING ACTUATOR

MODULATING ACTUATOR

Drawn By
MRG

Chk
DC

File Name
2105J2

Scale
NTS

Dwg No.

2105J2

Revision
1

Sheet
1/1

Date
01/05/02